



Hurricane Tough.

THE **ONLY** HURRICANE
ZONE EXTERIOR ACCESS
DOOR

+/- 80psf

The new Coastal Zone Exterior Access Door sets itself apart from the rest.

- Industry's Only High Velocity Wind Load + Impact Tested
- Design Pressure Performance of +/- 80psf
- Tested to Miami-Dade County Performance Requirements



Coastal Zone Door



Coastal Zone

EXTERIOR ACCESS DOOR

Nystrom's Coastal Zone Exterior Access Door provides efficient access from the exterior of your building without compromising security or weather resistance.

FEATURES

IMPACT, AIR + WIND PRESSURE TESTED Independent lab tested to TAS 201, 202 and 203 assures the best protection against the harshest elements.

TEMPERATURE CONTROL With 1.7 inches of closed cell polyurethane insulation, the Nystrom Coastal Zone Exterior Door delivers a R-11 thermal value.

CUSTOM SIZES Available in 1/4 inch increments from 18 inches by 18 inches to 36 inches by 48 inches maximum.



DETAILS

DOOR 24 gauge Galvanized Steel

FRAME 0.080 inch 6063-T5 Extruded Aluminum

SIZE

- Min: 18 inches by 18 inches
- Max: 36 inches by 48 inches

INSTALLATION Wall

FLANGE Exposed

HINGE Stainless Steel Continuous Piano

FINISH

- Door: Paint Ready Finish
- Frame: Mill

INSULATION 2 inch Polyurethane; R-11

GASKETING EPDM Self-Adhesive, Continuous

COMPLIANCE Tested to Miami-Dade County Performance Requirements

FLANGES



1 inch Flange

LATCHES



Locking Handle

ORDER GUIDE

BASE	WIDTH	X	LENGTH	MATERIAL	OPTIONS
XHTL		X		G	
	Standard Sizes (W x L)				C Drip cap
	18" x 18"		24" x 30"		
	20" x 30"		24" x 36"		
	24" x 24"		36" x 36"		

Rough opening is door size. Additional sizes available, call for more information.

Download Drawings, CAD, Specs, and LEED documents at www.nystrom.com